



CE-MARKERING

SLIDING GATE LOUVRES

SLIDING GATE LOUVRES

A louvered sliding gate offers a sleek, contemporary appearance that complements any location. The stylish horizontal louvres create a luxurious, closed design that provides both privacy and security. This way, you add elegance and protection to your entrance, without compromising on style.



TECHNICAL SPECIFICATIONS

Wheel Sets 2 tilting wheel sets with 9 enclosed ball-bearing wheels.

Top guide wheels rubber, Ø40 mm.

Gate Frame Bottom beam: 120x120 mm with welded rail profile 60x60 mm or 80x60 mm.

Infill Welded vertical box sections: 50x10 mm or 80x20 mm. Spacing approximately 60 mm.

Portals 1 drive portal + 1 catch portal on base plate, made from 80x80 mm box section.

Mounting Plate Includes 1 wheel set plate for installation of the rear wheel assembly.

Lock Locinox Sixtylock built-in lock with strike plate 2 aluminum cover plates for cylinder and handle set finish 1 standard handle set. Cylinder not included

Drop Bolts Both gate leaves fitted with internal drop bolts, positioned at the rear. Gate leaf with lock includes welded drop bolt bracket

Surface Treatment Galvanized according to NEN-EN-ISO 1461

Coating Powder coating, standard Category 1, in accordance with NEN 5254

OUR FENCING SYSTEMS ARE CE-CERTIFIED!

The sliding gates from HIS Gates fully comply with all European safety standards and are therefore CE-certified. Electric swing gates fall under the Machinery Directive MD 2006/42/EC, NEN-EN 13241, and NEN-EN 12453, ensuring that all potential hazards are properly safeguarded.

To prevent accidents, our gates meet the most stringent safety requirements and are equipped with the most reliable safety components. The CE certification guarantees that you have invested in a safe, compliant, and high-quality product.