



CE-MARKERING

SLIDING GATE MIKADO

SLIDING GATE MIKADO

The Mikado sliding gate is a true eye-catcher. With its playfully positioned diagonal bars, it offers not only security but also a modern and creative appearance. Its open design fits perfectly within both green and industrial environments, while the solid construction ensures long-lasting protection and durability.



TECHNICAL SPECIFICATIONS

Wheel Sets

- 2 tilting wheel sets with 9 enclosed ball-bearing wheels
- Top guide wheels: rubber, Ø40 mm

Gate Frame

- Bottom beam: 120x120 mm with welded rail profile
- Gate frame: 60x60 mm

Portals

- 1 drive portal and 1 catch portal on base plate, constructed from 80x80 mm box sections

Mounting Plate

- Includes 1 wheel set plate for installation of the rear wheel assembly

Bars

- Bars Ø25 mm, center-to-center max. 140 mm (variable)
- Welded through horizontal rails and cut straight

Foundation

- Dimensions depend on gate weight; available as prefab or cast in place.

FINISH

Surface Treatment: Galvanized according to NEN-EN-ISO 1461

Coating: Powder coating, standard

Category 1, in accordance with NEN 5254

OUR FENCING SYSTEMS ARE CE-CERTIFIED!

The sliding gates from HIS Gates fully comply with all European safety standards and are therefore CE-certified. Electric swing gates fall under the Machinery Directive MD 2006/42/EC, NEN-EN 13241, and NEN-EN 12453, ensuring that all potential hazards are properly safeguarded.

To prevent accidents, our gates meet the most stringent safety requirements and are equipped with the most reliable safety components. The CE certification guarantees that you have invested in a safe, compliant, and high-quality product.