



ORNEMENTAL FENCING FRIESLAND

ORNEMENTAL FENCING FRIESLAND

HIS Friesland stands out with its gracefully arched bars, giving the fence a refined and characterful appearance. A stylish choice for those who wish to combine security with a classic design.



Technical Specifications

Horizontal Rails 40x40 mm or 50x25x2 mm with holes for through-inserted bars.

Bars ø19 mm, standard spacing 100 mm center-to-center, with alternating curved bars.

Points Bars beneath the arch can be fitted with decorative spear tops.

Height Panel height plus 50 mm ground clearance.

Panel Width 1960 mm.

Posts 60x60 mm box sections with welded mounting brackets. The top of each post is sealed with a black plastic cap.

Optionally, posts can be fitted with a decorative post cap.

Finish

Installation Mounted using a bolt-and-nut connection.

Surface Treatment Standard hot-dip galvanized according to NEN-EN-ISO 1461.

Coating Powder coating available in all RAL colors (Category 1).

Optional Bars can be fitted with decorative spear tops.

Optioneel spijlen voorzien van sierpunten.

Type Friesland	Panel Dimensions	Rail Dimensions	Bar section	Points	Posts
Friesland 80	1960 x 750 mm	40 x 20 mm	Ø19 mm	No	60 x 60 L = 1500 mm
Friesland 100	1960 x 950 mm	40 x 20 mm	Ø19 mm	No	60 x 60 L = 1800 mm
Friesland 125	1960 x 1200 mm	40 x 20 mm	Ø19 mm	No	60 x 60 L = 2000 mm
Friesland 150	1960 x 1450 mm	40 x 20 mm	Ø19 mm	No	60 x 60 L = 2300 mm



Sphere ø30 mm



HP112



HP132



HP291