



TUBULAR FENCING SAFE

TUBULAR FENCING SAFE

HIS Safe is child-friendly and specially designed for environments with children, such as primary schools and daycare centers. The center-to-center spacing of the bars is 100 mm, preventing entrapment or slipping through. The legally required height for fencing around toddler or childcare facilities is 1250 mm.



Technical specifications

Horizontal Rails 50x25 mm or 40x40 mm with punched holes.
Bars For heights up to 2000 mm, bar diameter Ø25 mm.
Bar spacing: 100 mm center-to-center (75 mm between bars).
Height Panel height plus 50 mm ground clearance.
Panel Width 2940 mm.
Posts Robust 60x60 mm posts with pre-drilled holes for concealed or bracket connections. The top of each post is sealed with a black plastic cap.

Finish

Installation Each post is equipped with two transverse holes, allowing two bar panels to be connected using a bolt and nut.
Vandal-Resistant Option Optional stainless steel break nut to prevent unauthorized disassembly.
Fasteners All fastening materials are made of stainless steel.
Surface Treatment Standard hot-dip galvanized according to NEN-EN-ISO 1461.
Coating Powder coating available in all RAL colors (Category 1).

Fence type Safe	Panel Dimensions	Rail Dimensions	Bar diameter	Posts
Safe 100	2250 x 950 mm	50 x 25 mm	Ø 25 mm	60 x 60 L = 1900 mm
Safe 125	2250 x 1200 mm	50 x 25 mm	Ø 25 mm	60 x 60 L = 2100 mm
Safe 150	2250 x 1450 mm	50 x 25 mm	Ø 25 mm	60 x 60 L = 2400 mm
Safe 200	2250 x 1950 mm	50 x 25 mm	Ø 25 mm	60 x 60 L = 2900 mm

